

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 01/04/2022 Revision date: 04/13/2023 Version: 2.0

SECTION 1: Identification

1.1.	Identification		
Product f	orm	:	Mixture
Product r	ame	:	QUICKET

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Holcim Solutions and Products US, LLC 26 Century Boulevard, Suite 205 Nashville, Tennessee 37214 1-800-878-7876 • www.holcimersystems.com

1.4. Emergency telephone number

Emergency number

 For Chemical Emergency Spill, Leak, Fire, Exposure, or Incident CHEMTREC: Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture


GHS-US classification

Flammable liquids, Category 3	H226
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER, a doctor. P363 - Wash contaminated clothing before reuse. P370+P378 - In case of fire: Use media other than water to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

- 3.1. Substances
- Not applicable
- 3.2. Mixtures

mixtur

Name	Product identifier	%
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7	0.1 – 1
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	(CAS-No.) 82919-37-7	0.1 – 1
Benzene, 1,3-diisocyanatomethyl-	(CAS-No.) 26471-62-5	≤0.1

*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures			
4.1. Description of first aid measures			
First-aid measures general :	If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.		
First-aid measures after inhalation :	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.		
First-aid measures after skin contact	IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.		
First-aid measures after eye contact	IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.		
First-aid measures after ingestion :	IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.		
4.2. Most important symptoms and effects	a (acute and delayed)		
Symptoms/effects :	May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
Symptoms/effects after inhalation :	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
Symptoms/effects after skin contact :	May cause an allergic skin reaction.		
Symptoms/effects after eye contact :	Direct contact with eyes is likely to be irritating.		
Symptoms/effects after ingestion :	May cause gastrointestinal irritation.		
4.3. Immediate medical attention and special treatment, if necessary No additional information available			
SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishin	ig media		
Suitable extinguishing media	Carbon dioxide. Foam. Dry powder. Water spray. Sand.		

5.2. Specific hazards arising from the chemical		lical	
	Unsuitable extinguishing media	Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.	
	Suitable extinguishing media	Carbon doxide. I cam. Bry powder. Water spray. Cana.	

Fire hazard	:	Flammable liquid.
Explosion hazard	:	Product is not explosive.
Reactivity	:	Reacts slowly with water.

Γ

Safety Data Sheet

cording to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations 5.3. Special protective equipment and precautions for fire-fighters		
Precautionary measures fire	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.	
Protection during firefighting	 Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus. 	
Other information	: Under fire conditions closed containers may rupture or explode.	
SECTION 6: Accidental release me	easures	
6.1. Personal precautions, pr	otective equipment and emergency procedures	
General measures	: Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.	
6.1.1. For non-emergency pers	onnel	
Protective equipment	: Wear Protective equipment as described in Section 8.	
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responde	ers	
Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection.	
6.2. Environmental precautio	ns	
Prevent entry to sewers and public v	vaters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.	
6.3. Methods and material for	r containment and cleaning up	
For containment/cleaning up	: SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.	
	LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled motel contains for recovery or dispersed or remove with inert absorbent	

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage			
7.1.	Precautions for safe handling		
5		: Do not handle until all safety precautions have been read and understood. For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation).	
7.2.	Conditions for safe storage, in	ding any incompatibilities	
Techni	cal measures	: Empty containers retain product residue and can be hazardous.	
Storage	e conditions	: Store in a dry, cool and well-ventilated place. Protect from moisture. Keep container tightly closed.	
Heat a	nd ignition sources	: Avoid ignition sources.	

spilled material or used absorbent.

Special rules on packaging : Keep only in original container.

covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)			
ACGIH	Remark (ACGIH)	OELs not established	
OSHA	Remark (OSHA)	OELs not established	
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)			
ACGIH	Remark (ACGIH)	OELs not established	
OSHA	Remark (OSHA)	OELs not established	
Benzene, 1,3-diisocyanatomethyl- (26471-62-5)			
ACGIH	ACGIH OEL TWA [ppm]	0.001 ppm inhalable fraction and vapor	
ACGIH	ACGIH OEL STEL [ppm]	0.005 ppm inhalable fraction and vapor	
OSHA	Remark (OSHA)	OELs not established	

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing. In case of inadequate ventilation wear respiratory protection.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where dust exceeds PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment. Respirator with organic cartridge.

SECTION 9: Physical and chemical properties	
---	--

9.1.	9.1. Information on basic physical and chemical properties			
Physical state		: Liquid		
Appearance		: Liquid		
Color		: White		
Odor		: Mildly aromatic		
Odor threshold		: No data available		
рН		: No data available		
Melting p	point	: No data available		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 54.4 °C (130 °F) (Pensky-Martens Closed Cup)
Relative evaporation rate (n-butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: >1
Relative density	: No data available
Density	: 9.6 lb/gal ±0.2 lb/gal
Solubility	: Stable. Will react slowly with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts slowly with water.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

High temperatures, incompatible materials.

10.5. Incompatible materials

Water. Alcohols. Amines. Acids. Alkalis.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides. Isocyanates. Hydrogen cyanide.

Carbon monoxide. Carbon dioxide. Milloger	
SECTION 11: Toxicological information	
11.1. Information on toxicological eff	ects
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) set	bacate (41556-26-7)
LD50 oral rat 2615 mg/kg	
Benzene, 1,3-diisocyanatomethyl- (26471	-62-5)
LD50 oral rat	3060 mg/kg
LD50 dermal rabbit	10000 mg/kg
LC50 Inhalation - Rat	0.099 mg/l/4h dust and mist
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

: Not classified : Not classified

Germ cell mutagenicity Carcinogenicity

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cording to Federal Register / Vol. 77, No. 58 / Monday	
Γitanium dioxide (13463-67-7)	
ARC group	2B - Possibly carcinogenic to humans
n OSHA Hazard Communication Carcinogen ist	Yes
Benzene, 1,3-diisocyanatomethyl- (26471-62-	-5)
ARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
/iscosity, kinematic	: No data available
Symptoms/effects	: May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Direct contact with eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: No information available.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	
SECTION 13: Disposal considerations I3.1. Disposal methods	
•	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

SECTION 14: Transport information

Department of Transportation (DOT)

This mixture meets the requirements for 49 CFR 173.150(f) exemptions and the outer packages of this material would not require transportation labeling.

Transport by sea (IMDG)

Transport document description (IMDG)	: UN 1263 PAINT, 3, III
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport (IATA)

Transport document description (IATA)	: UN 1263 Paint, 3, III
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

QUICKET

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA

	CADA Continue 244/242 Unerged Classes	
	SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization
- 1		

15.2. International regulations

No additional information available

15.3. US State regulations

⚠	WARNING:
---	----------

This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Titanium dioxide (13463-67-7)	Х				Not available	
Benzene (71-43-2)	X	X	x		6.4 μg/day (oral); 13 μg/day (inhalation)	24 μg/day (oral); 49 μg/day (inhalation)
Cumene (98-82-8)	Х					
Benzene, 1,3- diisocyanatomethyl- (26471-62-5)	x					
Propylene oxide (75- 56-9)	Х					
Acetaldehyde (75-07- 0)	х				90 (inhalation)	
Formaldehyde (50-00- 0)	х				40 µg/day	
Ethylene oxide (75-21- 8)	Х	Х	х	х	2 µg/day	20 µg/day
1,4-Dioxane (123-91- 1)	Х				30 µg/day	
Toluene (108-88-3)		X				7000 µg/day
Tetrachloromethane (56-23-5)	X					

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations	
Titanium dioxide (13463-67-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List	
Benzene (71-43-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List	
Cumene (98-82-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances	
Maleic anhydride (108-31-6)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Phenol (108-95-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Silica, amorphous (7631-86-9)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List	
Benzene, 1,2,4-trimethyl-(95-63-6)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Aluminum oxide (1344-28-1)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Magnesium oxide (1309-48-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Benzene, 1,3-diisocyanatomethyl-(26471-62-5)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Dibutyltin dilaurate (77-58-7)	U.S Pennsylvania - RTK (Right to Know) List; U.S New Jersey - Right to Know Hazardous Substance List	
Zirconium oxide (1314-23-4)	U.S Massachusetts - Right To Know List	
Toluene (108-88-3)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List	
Formaldehyde (50-00-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List	
Propylene oxide (75-56-9)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Acetaldehyde (75-07-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
1,4-Dioxane (123-91-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Ethylene oxide (75-21-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List	
Tetrachloromethane (56-23-5)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Dimethyl sulfoxide (67-68-5)	U.S New Jersey - Right to Know Hazardous Substance List	

SECTION 16: Other information

Revision date Other information : 04/13/2023

: Author: JMM.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur. NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures. HMIS Hazard Rating Health : 2* Health : 2* Flammability : 1 Physical : 1		
NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures. HMIS Hazard Rating Health : 2* Health * - Chronic (long-term) health effects may result from repeated overexposure Flammability : 1	NFPA health hazard	
HMIS Hazard Rating Health : 2* Health : - Chronic (long-term) health effects may result from repeated overexposure Flammability : 1	NFPA fire hazard	
Health : 2* Health * - Chronic (long-term) health effects may result from repeated overexposure Flammability : 1	NFPA reactivity	
Health * - Chronic (long-term) health effects may result from repeated overexposure Flammability : 1	HMIS Hazard Rating	
Flammability : 1	Health	: 2*
	Health	* - Chronic (long-term) health effects may result from repeated overexposure
Physical : 1	Flammability	: 1
	Physical	: 1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.